Other Measurements recorded by measurer

Overall Length

Overhang Forward to L

Overhang Aft to L

Total Overhang (Sum overhang forward and aft)

Waterline Length (Overall Length - Total Overhang)

Minimum measured cockpit frame over water level when ballasted and swamped in accordance with rule C.5.2

Boat weight recorded by weighing according to rule C.5.1

Boat weight including 35 kg ballast

Minimum weight by Rule D.7.2 $(0.2xLWL+0.06)^3 \times 1025$

	4,18
+0,547	
+0,655	
\rightarrow	-1,202
	2,978
	0,050
	254 Kg
	289 Kg
	289 Kg


Sail Dimensions

P = 4,65

Outer point distance E = 1.9c

Forestay height I = 3.75Foretriangle base J = 1.50

Mast measurements checked	OR
Height of mast datum point Rule C.8.2 (b) (2)	36
Boom measurements checked	OK
Rudder thickness, Rule E.4.3	35



Areas of Sail

Mainsail $0.5 \times P \times E =$

Foretriangle Total $0.5 \times I \times J =$

Foretriangle Total x 0.85

Sail Area For Rating = S = VS

	4,557 m ²
$2,925 \text{ m}^2$	
	2.484 m2
	7,043 m ²
	2,654



Builder CHARGER COMPOSITED Designer NORLIN

When Built. 2009

Measured by Tom Brown Date of Measurement 23.04, 2009 (FYA 0054)

Complementary measured by...... Date of compl measurement......

Certificate issued by . JOHN . SEEPE ... Date of issue ... 10 28 22

CA US 2.4MR CLASS VICE- PRES. authority

signature